

Cleco[®]
Production Tools

CellCore[™]
Cordless Assembly Tools

EASY TO HANDLE. HARD TO BREAK.



THE SMARTEST TOOL FOR THE TOUGHEST ENVIRONMENT

CellCore™ puts you in control with cordless assembly tools that are **easy to handle**, and **hard to break**.

Cleco's new CellCore™ Cordless Assembly Tools are smart, durable and designed to withstand the toughest environments. The lightweight ergonomic design reduces operator fatigue while delivering state-of-the-art power, weight and balance. A large user interface makes it quick and easy to program rundowns on the tool without a controller.



Durable - Assembly line tough
(Drop tested up to 5 feet)



Reliable - Increases uptime with 500k cycles
between maintenance



Ergonomic - Reduces operator fatigue while
delivering state-of-the-art power and intelligence



Easy to Use - Large user interface allows easy
on-the-tool programming without a controller

EASY TO HANDLE. HARD TO BREAK.



CellCore is the most versatile, easy-to-use cordless tool in the industry.

Users can program up to 10 rundown strategies, called "FastApps", directly on the tool in standalone mode. Users can also pair CellCore tools with Cleco's new mPro200 controller. By pairing the devices, users can easily capture data in real time and program advanced rundowns within a much more compact footprint.

THE SMARTEST TOOL FOR THE TOUGHEST ENVIRONMENT



CellCore High Torque



-  **FastApps** - Program up to 10 applications directly on the tool or connect to a controller for maximum functionality
-  **Versatile** - 40-2000Nm range allowing more flexibility in your tool
-  **Reliable** - Norbar® torque multiplier provides proven accuracy and quality
-  **Access** - 360° rotating head and handle for maximum accessibility

**ALL
NEW**

PISTOL



MODEL NUMBER	TORQUE RANGE (Nm) Min-Max	TORQUE RANGE (ft-lb) Min-Max	SPEED r/min	WEIGHT* kg (lb)	LENGTH mm (in)	SIDE TO CENTER mm (in)	HEIGHT mm (in)	OUTPUT
CCBPW04Q	1.2 - 4	0.9 - 2.9	2480	0.98 (2.16)	185 (7.27)	29 (1.14)	204 (8.03)	1/4" Hex Quick Change
CCBPW12Q	3.6 - 12	2.7 - 8.8	800	1.05 (2.32)	201 (7.89)	29 (1.14)	204 (8.03)	1/4" Hex Quick Change
CCBPW123	3.6 - 12	2.7 - 8.8	800	1.05 (2.32)	198 (7.79)	29 (1.14)	204 (8.03)	3/8" Square Drive
CCBPW22Q	6.6 - 22	4.9 - 16.2	430	1.05 (2.32)	201 (7.89)	29 (1.14)	204 (8.03)	1/4" Hex Quick Change
CCBPW223	6.6 - 22	4.9 - 16.2	430	1.05 (2.32)	198 (7.79)	29 (1.14)	204 (8.03)	3/8" Square Drive



RIGHT ANGLE

MODEL NUMBER	TORQUE RANGE (Nm) Min-Max	TORQUE RANGE (ft-lb) Min-Max	SPEED r/min	WEIGHT* kg (lb)	LENGTH mm (in)	SIDE TO CENTER mm (in)	HEIGHT mm (in)	OUTPUT
CCBAW153	4.5 - 15	3.3 - 11.0	570	1.70 (3.75)	456 (17.95)	31.8 (1.25)	88 (3.46)	3/8" Square Drive
CCBAW253	7.5 - 25	5.5 - 18.4	305	1.70 (3.75)	456 (17.95)	31.8 (1.25)	88 (3.46)	3/8" Square Drive
CCBAW353	10.5 - 35	7.7 - 25.8	255	1.95 (4.30)	486 (19.15)	31.8 (1.25)	92 (3.63)	3/8" Square Drive
CCBAW503	15 - 50	11.1 - 36.8	165	2.00 (4.41)	499 (19.65)	31.8 (1.25)	92 (3.63)	3/8" Square Drive

CELLCORE HIGH TORQUE



MODEL NUMBER	TORQUE RANGE (Nm) Min-Max	TORQUE RANGE (ft-lb) Min-Max	SPEED r/min	WEIGHT* kg (lb)	LENGTH mm (in)	SIDE TO CENTER mm (in)	HEIGHT mm (in)	OUTPUT
CCBPWN200D6	40-200	29.5-147.5	42	3.36 (7.41)	339 (13.35)	28 (1.10)	204 (8.03)	3/4" Square Drive
CCBPWN500D6	119-500	87.8-368.8	14	3.36 (7.41)	339 (13.35)	28 (1.10)	204 (8.03)	3/4" Square Drive
CCBPWN1000D6	214-1000	157.8-737.6	8	6.68 (14.73)	403 (15.87)	40 (1.57)	208 (8.19)	3/4" Square Drive
CCBPWN1350D8	293-1350	216-995.7	6	6.68 (14.73)	403 (15.87)	40 (1.57)	208 (8.19)	1" Square Drive
CCBPWN2000D8	436-2000	321.6-1475	4	6.68 (14.73)	403 (15.87)	40 (1.57)	208 (8.19)	1" Square Drive

CONTROLLERS†



MODEL NUMBER	DESCRIPTION	TOOL COMPATIBILITY	WEIGHT kg (lb)	WIDTH mm (in)	HEIGHT mm (in)	DEPTH mm (in)
mPro200GC	Controller	CellCore, LiveWire, I-Wrench	3.23 (7.1)	113 (4.4)	340 (13.4)	320 (12.6)
mPro200GC-AP	Controller with Access Point	CellCore, LiveWire, I-Wrench	3.43 (7.5)	113 (4.4)	340 (13.4)	320 (12.6)
mPro200GC-G	Controller (Global)	CellCore, LiveWire, I-Wrench	3.23 (7.1)	113 (4.4)	340 (13.4)	320 (12.6)
mPro200GC-AP-G	Controller with Access Point (Global)	CellCore, LiveWire, I-Wrench	3.43 (7.5)	113 (4.4)	340 (13.4)	320 (12.6)

†also compatible with the mPro400 Global Controller Platform

ACCESSORIES



MODEL NUMBER	DESCRIPTION	MODEL NUMBER	DESCRIPTION
T50-1000497	18V, 2.0Ah Battery (.43kg/.94lb)	T50-1000508	18V 6-Bay Sequential Charger (Europe, Middle East, Africa)
T50-1000498	18V, 5.0Ah Battery (.72kg/1.60lb)	T50-1000543	18V Charger (Argentina)
T50-1000499	18V Rapid Charger (NA)	T50-1000544	18V Rapid Charger (United Kingdom)
T50-1000500	18V 6-Bay Sequential Charger (NA)	T50-1000545	18V Rapid Charger (China)
T50-1000506	18V Rapid Charger (Europe, Middle East, Africa)	T50-1000546	18V Rapid Charger (Japan)
T50-1000507	18V Charger (Brazil)	T50-1000547	18V 6-Bay Sequential Charger (United Kingdom)

*weight values do not include battery

The Americas

Apex Tool Group
670 Industrial Drive
Lexington, SC 29072
USA
Tel.: +1 (800) 845 5629
Tel.: +1 (919) 387 0099
Fax: +1 (803) 358 7681
www.ClecoTools.com

Apex Tool Group
Manufacturing México
S. de R.L. de C.V.
Validad El Pueblito #103
Parque Industrial Querétaro
Querétaro, QRO 76220
México
Tel.: +52 (442) 211 3800
Fax: +52 (800) 685 5560

Apex Tool Group
Ind. Com. Ferram. Ltda. Av.
Liberdade, 4055
Zona Industrial Iporanga
Sorocaba, São Paulo
CEP# 18087-170
Brazil
Tel.: +55 15 3238 3870
Fax: +55 15 3238 3938

Europe | Middle East | Africa

Apex Tool Group GmbH
Industriestraße 1
73463 Westhausen
Germany
Tel.: +49 (0) 73 63 81 0
Fax: +49 (0) 73 63 81 222
www.ClecoTools.de

Apex Tool Group SAS
25 Avenue Maurice Chevalier
77330 Ozoir-La-Ferrière
France
Tel.: +33 16 44 32 200
Fax: +33 16 44 317 17

Apex Tool Group
Hungaria Kft.
Pálfiafa u.2
9027 Győr
Hungary
Tel.: +36 96 66 1383
Fax: +36 96 66 1135

Asia Pacific

Apex Power Tool Trading
(Shanghai) Co., Ltd.
2nd Floor, Area C
177 Bi Bo Road
Pu Dong New Area, Shanghai
China 201203 P.R.C.
Tel.: +86 21 60880320
Fax: +86 21 60880298

Apex Power Tools India
Private Limited
Gate No. 1, Plot No. 5
S. No. 234, 235 & 245
Indialand Global Industrial Park
Taluka-Mulsi, Phase I
Hinjawadi, Pune 411057
Maharashtra, India
Tel.: +91 020 66761111